



5012-SUR Outdoor Subscriber Unit



5012-SUI Indoor Subscriber Unit  
(antenna not pictured)

### Outdoor Broadband Wireless Access

Proxim Wireless offers the industry's most complete suite of outdoor broadband wireless access products. This portfolio includes:

- **Tsunami™ MP.11** – capabilities of fixed and mobile WiMAX for U.S. and global markets
- **Tsunami™ MP.16** – WiMAX for the 3.5 GHz frequency band
- **ORiNOCO® Wi-Fi Mesh** – Outdoor and indoor Wi-Fi mesh for service providers and municipalities

**Proxim Wireless** is a global pioneer in scalable broadband wireless networking. From Wi-Fi to wireless Gigabit Ethernet – our WLAN, mesh, point-to-multipoint and point-to-point products are available through our extensive global channel network.

**The industry-leading Tsunami™ MP.11 product line – providing the capabilities of fixed and mobile WiMAX for license-free frequency bands worldwide – has been extended to include an economical series of subscriber units ideal for large scale wireless deployments.**

Proxim Wireless is a leader and an early innovator in wireless technology for providing high-speed, long-range broadband wireless access to complement Wi-Fi® networks. The MP.11 product line has enabled municipalities and service providers to bridge the digital divide, increase productivity, cut network costs, and create new business opportunities — all through WiMAX features for license-free frequency bands worldwide. Consisting of an indoor and outdoor form factor, the 5012 series of subscriber units is designed specifically for the residential market and accelerates the service provider's break-even point, making this product ideal for large-scale wireless deployments.

---

#### MP.11 5012 Subscriber Unit Features:

- Indoor, self-installable form factor and outdoor, ruggedized form factor
- Throughput comparable to or better than cable/DSL: 12 Mbps aggregate throughput
- Aggressive ROI and fast payback for large-scale deployments
- Power over Ethernet support
- Designed for quick and easy installation – Indoor subscriber unit bundled with 15 dBi window antenna and outdoor unit contains 18 dBi integrated antenna
- Compatible with existing MP.11 5054, 5054-R and 5054-R-LR Base Station Units

---

#### MP.11 System Features:

- License-free frequency bands worldwide: supports 5.15-5.35 GHz, 5.47-5.725 GHz and 5.725-5.850 GHz frequency bands
- Scheduled media access controller (MAC), also known as polling: enables a base station to hear all subscriber units, preventing nodes from interfering with each other and increasing system throughput
- Orthogonal frequency division multiplexing (OFDM): enhances non-line-of-sight performance improving deployment in challenging areas
- Quality of Service (QoS): supports voice, video and data converged networking
- RADIUS-based bandwidth management: deliver multiple service plans
- Asymmetric bandwidth management: increases service provider revenue through creation of uplink bandwidth tiers
- Dynamic Data Rate Selection (DDRS): maximizes subscriber coverage by allowing each subscriber to receive the maximum data rate possible
- Dynamic Frequency Selection (DFS): prevents interference with other systems; for 5.4 GHz, MP.11 has achieved ETSI EN 301-893 v1.3.1 certification
- Security: advanced encryption with AES protects over-the-air transmission; intracell blocking forbids direct communication between subscriber units
- Deployment tools: antenna alignment and remote management and configuration eliminate the need for truck rolls

# Tsunami MP.11-5012 Series Technical Specifications

## FEATURES

### PERFORMANCE AND SCALABILITY

|                                     |  |
|-------------------------------------|--|
| Best-in-class Performance with WORP | By eliminating in-the-air collisions and maximizing data content for each transmission, Wireless Outdoor Router Protocol (WORP) significantly improves performance |
| Near Line of Sight Capable          | Line of sight and near line of sight connectivity extends deployment flexibility in rural as well as high-density urban areas                                      |

### QUALITY OF SERVICE (QoS)

|   |  |
|---|--|
| WiMAX 802.16 QoS                            | Supports up to 8 QoS Classes; Supports up to 8 Service Flows per class   |
| Traffic Prioritization Parameters Supported | IP ToS (Layer 3 QoS identification), IP Protocol List, 802.1p tag (Layer 2 QoS identification), Source IP Address+Mask, Destination IP Address+Mask, Source TCP/UDP port ranges, Destination TCP/UDP port ranges, Source MAC addresses, Destination MAC address, VLAN ID, Ether type |
| Committed Information Rate (CIR)            | Users can set CIR for each Subscriber Unit   |
| Minimum Information Rate (MIR) Support      | User defined MIR   |

### SECURITY

|  |   |
|--|---|
| Unicast, Multicast and Broadcast Storm | User definable threshold levels prevent excessive bandwidth consumptions from degrading network control performance           |
| Packet Filtering                       | MAC, Ether type, IP address filtering provides very granular network security   |
| Intracell Blocking                     | Allows the BSU to act as the central policy enforcer for SU to SU communications, further enhancing subscriber units' privacy |
| Secure Encryption and Authentication   | Support for WEP, WEP+ and AES for "over the air" encryption and Radius for user authentication                                |
| Interference Mitigation Tool           | Variable Receive Threshold, Transmit Power Control and Dynamic Frequency Selection  |

### LOWER COST OF OWNERSHIP

|                                       |  |
|---------------------------------------|--|
| Dynamic Data Rate Selection (DDRS)    | Automatically optimizes throughput as link conditions change or as subscribers roam; connectivity is automatically maintained when link quality degrades |
| Flexible and Secure Remote Management | Supports remote management via Telnet, SNMP and web interfaces with password protections   |
| Antenna Alignment Tool                | Provides running statistics with real time signal strength to aid antenna installation   |
| Comprehensive Station Statistics      | Unit and group statistics are available for monitoring, planning and management of a wireless network  |

| PRODUCT MODELS                                 |   |  | ENVIRONMENTAL              | 5012-SUI   | 5012-SUR              |
|--|---|--|----------------------------|--|-----------------------|
| 5012-SUI-WA-XX                                 | Tsunami MP.11 Model 5012 Indoor Subscriber Unit bundled with 15 dBi Window Antenna  |  | TEMPERATURE:<br>OPERATING  | 0° to 50°C   | -33° to 60°C          |
| 5012-SUR-XX                                    | Tsunami MP.11 Model 5012 Outdoor Subscriber Unit with 18 dBi Integrated Antenna   |  | STORAGE                    | -10° to 70°C   | -44° to 80°C          |
| <b>RADIO &amp; TRANSMISSION SPECIFICATIONS</b> |   |  | HUMIDITY                   | 95% (non-condensing)   | 100% (non-condensing) |
| MODULATION METHOD                              | OFDM  |  | <b>ELECTRICAL</b>          |  |                       |
| FREQUENCY BANDS                                | Americas (FCC): 5.25-5.35 GHz (15 channels)<br>Americas (FCC): 5.725-5.850 GHz (21 channels)<br>Europe (ETSI): 5.47-5.725 GHz (46 channels)<br>Europe (Russia): 5.15-5.850 GHz (82 channels)<br>Europe (Licensed in the UK): 5.725- 5.850 GHz (21 channels) |  | INPUT                      | 110 to 240 VDC power 5V (SUI Only)   |                       |
| <b>INTERFACES</b>                              |   |  | POWER OVER ETHERNET        | Via RJ-45 Ethernet interface port 802.3af compliant  |                       |
| WIRED ETHERNET                                 | Wired Ethernet 10/100Base-TX Ethernet (RJ-45)   |  | <b>MANAGEMENT</b>          |  |                       |
| ANTENNA CONNECTOR                              | 5012-SUI: N-Male terminated pigtail; 5012-SUR: N/A  |  | LOCAL                      | RS-232 serial (RJ11 and DB-9)  |                       |
| ANTENNA GAIN                                   | 5012-SUI: 15 dBi external window antenna;<br>5012-SUR: 18 dBi integrated antenna  |  | REMOTE                     | Telnet Web GUI, TFTP   |                       |
| DATA RATE                                      | 54, 48, 36, 24, 18, 12, 9, 6, 4.5, 3, 2.25, 1.5 Mbps  |  | SNMP                       | SNMPv1/v2; MIB-II ; Ethernet-like MIB; BridgeMIB; 802.3MAU; 802.11 MIB; Private MIB; ORINOCO MIB; RFC 1157; RFC 1213; RFC 1643; RFC 1493; RFC 2668   |                       |
| OVER-THE-AIR THROUGHPUT                        | Maximum 12 Mbps   |  | <b>LEDS</b>                | Power, Radio Activity, Ethernet Activity   |                       |
| TX POWER                                       | Up to 18 dBm  |  | <b>MTBF &amp; WARRANTY</b> | >100,000 hours; 1 year parts and labor   |                       |
| <b>UNIT PHYSICAL</b>                           | <b>5012-SUI-WA</b>  | <b>5012-SUR</b>                              | <b>PACKAGE CONTENTS</b>    | 5012-SUI-WA<br>5012-SUI Indoor Subscriber unit, N-type Male terminated pigtail, 15 dBi window antenna, Wall Mountable DC power supply, Mounting bracket for ceiling or wall mounting, Quick Install Guide and CD with documentation and regulatory guide |                       |
| DIMS:  |   |  | 5012-SUR                   | 5012-SUR Outdoor Subscriber unit with 18 dBi integrated antenna, Band Clamps for pole mount, Quick Install Guide and CD with documentation and regulatory guide  |                       |
| PACKAGED                                       | 14.3 x 7.6 x 4.4 in<br>(363 x 193 x 112 mm)   | 13.9 x 11.1 x 6.1 in<br>(353 x 282 x 155 mm) | <b>ADD'T'L ACCESSORIES</b> | Universal Mounting Bracket for wall mounting (Part #1087-UMK), Active Ethernet Injector (4301-XX)  |                       |
| UNPACKAGED                                     | 7.8 x 4.75 x 1.0 in<br>(198 x 121 x 25 mm)  | 4.0 x 8.5 x 10.2 in<br>(98 x 215 x 259 mm)   | <b>RELATED PRODUCTS</b>    | Tsunami MP.11 5054 Base Station (5054-BSU, 5054-BSUR or 5054-BSUR-LR), Tsunami MP.11 5054 Subscriber Station (5054-SU, 5054-SUR or 5054-SUA), 5 GHz Window or Panel Antennas, ServPak for enhanced support, ProximVision™ NMS                            |                       |
| WEIGHT:  |   |  |                            |  |                       |
| PACKAGED                                       | 3.52 lbs (1.6 kg)   | 3.3 lbs (1.5 kg)                             |                            |  |                       |
| UNPACKAGED                                     | 0.65 lbs (0.29 kg)  | 2.4 lbs (1.02 kg)                            |                            |  |                       |

For detailed technical specifications, please go to <http://www.proxim.com>

©2007 Proxim Wireless Corporation. All rights reserved. Proxim is a registered trademark and the Proxim logo and Tsunami are trademarks of Proxim Wireless Corporation. All other trademarks mentioned herein are property of their respective owners. Specifications are subject to change without notice.

DS\_0407\_MP115012\_A4



Proxim Wireless Corporation  
[www.proxim.com](http://www.proxim.com)